Blizzard™

PRODUCT SPECIFICATION SHEET

Product	**BCC2PREPGRANITE** Compact Double Door Refrigerated Pizza Prep Counter
Warranty	3 Year Warranty

COMPLIANCE	
County of Manufacture	China
GTIN	5060486682157
Commodity Code	8418509090
UKCA	Yes
CE	Yes

DELIVERY	
Special Order Unit	No
Modified Unit	No
Delivery Group	T1-G2
Default Carrier	9 - Hadfields
Next Day Delivery	No

PACKAGING & SHIPPING			
Packaging Height (mm)	730	Waste Cardboard Packaging (KG)	2.8
Packaging Width (mm)	1260	Waste Plastic Packaging (KG)	0.1
Packaging Depth (mm)	930	Waste Wood Packaging (KG)	19

MEASUREMENTS & CAPACITY			
External Unit Height (mm)	1086	Net Weight (kg)	106
External Unit Width (mm)	903	Gross Weight (kg)	118
External Unit Depth (mm)	700	Net Capacity (L)	TBC
Internal Unit Height (mm)	TBC	Gross Capacity (L)	240
Internal Unit Width (mm)	TBC	Display Capacity (M^2)	N/A
Internal Unit Depth (mm)	TBC		

TEMPERATURE	
Temperature Range	+2°C ~ +8°C
Max Ambient Temperature	TBC
Climate Class	4

PLUMBING & WATER	
Water Required	No
Water Usage (L)	N/A
Drainage Required	No

Blizzard™

PRODUCT SPECIFICATION SHEET

ELECTRICAL & ENERGY			
Power Supply	13amp	KWH Annum	N/A
Power Consumption (W)	170	EEI	N/A
Rated Current (A)	1.2	Storage Energy Rating	N/A
KWH Per 24/hr	N/A	Display Energy Rating	N/A

FURTHER DETAILS			
Finish	Stainless Steel	Cooling	Fan Assisted
Alternative Finish	N/A	Refrigerant	R600a
Material	Stainless Steel	Refrigerant Amount (g)	65
Internal Material	Stainless Steel	Defrost	Automatic
Number Of Doors	2	Noise Level (db)	42
Door Type	Hinged	Production 24/hr	N/A
Number Of Drawers	N/A	Ice Type	N/A
Nightblind	No	Ice Size (mm)	N/A
Shelves Supplied	2	Bin Capacity (kg)	N/A
Shelf Width (mm)	TBC	Requires Construction	No
Shelf Depth (mm)	TBC	Slot Size (mm)	N/A
Deck Size	TBC	Grill Size (mm)	N/A
Basket Capacity	TBC	Bottle Capacity	N/A
Basket Supplied	TBC	Glass Capacity	N/A
Basket Size	TBC	Dish Capacity	N/A
Container Capacity	5 x GN 1/6	Baskets Per Hour	N/A
Containers Supplied	0	Keg Capacity	N/A
Controller	Digital Controller	Bowl Capacity	N/A
Controller Type	Dixell	ETL Accredited	No