Blizzard™

PRODUCT SPECIFICATION SHEET

Product	**BCC3-GR-TOP** Compact Triple Door Counter Refrigerator With Granite Worktop
Warranty	3 Year Warranty

COMPLIANCE	
County of Manufacture	China
GTIN	5060486684052
Commodity Code	8418509090
UKCA	Yes
CE	Yes

DELIVERY	
Special Order Unit	No
Modified Unit	No
Delivery Group	T1-G3
Default Carrier	9 - Hadfields
Next Day Delivery	No

PACKAGING & SHIPPING			
Packaging Height (mm)	730	Waste Cardboard Packaging (KG)	3.2
Packaging Width (mm)	1050	Waste Plastic Packaging (KG)	0.1
Packaging Depth (mm)	1390	Waste Wood Packaging (KG)	16

MEASUREMENTS & CAPACITY			
External Unit Height (mm)	866	Net Weight (kg)	110
External Unit Width (mm)	1368	Gross Weight (kg)	126
External Unit Depth (mm)	700	Net Capacity (L)	219
Internal Unit Height (mm)	TBC	Gross Capacity (L)	368
Internal Unit Width (mm)	TBC	Display Capacity (M^2)	N/A
Internal Unit Depth (mm)	TBC		

TEMPERATURE	
Temperature Range	+2°C ~ +8°C
Max Ambient Temperature	TBC
Climate Class	4

PLUMBING & WATER	
Water Required	No
Water Usage (L)	N/A
Drainage Required	No

Blizzard™

PRODUCT SPECIFICATION SHEET

ELECTRICAL & ENERGY			
Power Supply	13amp	KWH Annum	1432
Power Consumption (W)	240	EEI	61
Rated Current (A)	1.6	Storage Energy Rating	D
KWH Per 24/hr	3.9	Display Energy Rating	N/A

FURTHER DETAILS			
Finish	Stainless Steel	Cooling	Fan Assisted
Alternative Finish	N/A	Refrigerant	R290
Material	Stainless Steel	Refrigerant Amount (g)	78
Internal Material	Stainless Steel	Defrost	Automatic
Number Of Doors	3	Noise Level (db)	42
Door Type	Hinged	Production 24/hr	N/A
Number Of Drawers	N/A	Ice Type	N/A
Nightblind	No	Ice Size (mm)	N/A
Shelves Supplied	3	Bin Capacity (kg)	N/A
Shelf Width (mm)	TBC	Requires Construction	No
Shelf Depth (mm)	TBC	Slot Size (mm)	N/A
Deck Size	N/A	Grill Size (mm)	N/A
Basket Capacity	N/A	Bottle Capacity	N/A
Basket Supplied	N/A	Glass Capacity	N/A
Basket Size	N/A	Dish Capacity	N/A
Container Capacity	N/A	Baskets Per Hour	N/A
Containers Supplied	N/A	Keg Capacity	N/A
Controller	Digital Controller	Bowl Capacity	N/A
Controller Type	Dixell	ETL Accredited	No