Blizzard™

PRODUCT SPECIFICATION SHEET

Product	**BTD250SSGDV2** 2.5m Multideck With Sliding Glass Doors
Warranty	3 Year Warranty

COMPLIANCE	
County of Manufacture	China
GTIN	5060486685806
Commodity Code	8418501990
UKCA	Yes
CE	Yes

DELIVERY	
Special Order Unit	No
Modified Unit	No
Delivery Group	T1-G5
Default Carrier	9 - Hadfields
Next Day Delivery	No

PACKAGING & SHIPPING			
Packaging Height (mm)	2180	Waste Cardboard Packaging (KG)	50
Packaging Width (mm)	2630	Waste Plastic Packaging (KG)	0.1
Packaging Depth (mm)	870	Waste Wood Packaging (KG)	50

MEASUREMENTS & CAPACITY			
External Unit Height (mm)	2000	Net Weight (kg)	480
External Unit Width (mm)	2565	Gross Weight (kg)	580
External Unit Depth (mm)	800	Net Capacity (L)	1500
Internal Unit Height (mm)	1296	Gross Capacity (L)	1634
Internal Unit Width (mm)	2500	Display Capacity (M^2)	4.3
Internal Unit Depth (mm)	652		

TEMPERATURE	
Temperature Range	-1°C ~ +5°C
Max Ambient Temperature	25°C
Climate Class	3

PLUMBING & WATER	
Water Required	No
Water Usage (L)	N/A
Drainage Required	No

Blizzard™

PRODUCT SPECIFICATION SHEET

ELECTRICAL & ENERGY			
Power Supply	2 x 13amp	KWH Annum	6552
Power Consumption (W)	1140	EEI	32.3
Rated Current (A)	6.8	Storage Energy Rating	N/A
KWH Per 24/hr	17.95	Display Energy Rating	C

FURTHER DETAILS			
Finish	Stainless Steel	Cooling	Ventilated
Alternative Finish	N/A	Refrigerant	R290
Material	Stainless Steel	Refrigerant Amount (g)	150
Internal Material	Stainless Steel	Defrost	Automatic
Number Of Doors	4	Noise Level (db)	70
Door Type	Sliding	Production 24/hr	N/A
Number Of Drawers	N/A	Ice Type	N/A
Nightblind	No	Ice Size (mm)	N/A
Shelves Supplied	4	Bin Capacity (kg)	N/A
Shelf Width (mm)	450	Requires Construction	No
Shelf Depth (mm)	1248	Slot Size (mm)	N/A
Deck Size	N/A	Grill Size (mm)	N/A
Basket Capacity	N/A	Bottle Capacity	N/A
Basket Supplied	N/A	Glass Capacity	N/A
Basket Size	N/A	Dish Capacity	N/A
Container Capacity	N/A	Baskets Per Hour	N/A
Containers Supplied	N/A	Keg Capacity	N/A
Controller	Digital Controller	Bowl Capacity	N/A
Controller Type	Dixell	ETL Accredited	No